

TECHNICAL DATA SHEET EWB 3460**Geared Motor:**

- Manufacturer / Type: 2 x HASEN SICF56B3,8-180L-4G-V1
- Power: 2 x 22,0 Kw
- Output speed: 1.430 rpm
- Voltage: 400 / 690 V / 50 Hz
- Output geared speed: 373 rpm
- Protection / Class: IP 65 / F
- Assembly position: V1

Axial Fan:

- Manufacturer / Type: 2 x ILMED / 32n-7-E1n-2720-AP
- No. of blades: 7
- Blade material: Sea proof aluminium.
- Potencia absorbida: 2 x 16,5 Kw
- Caudal / Presión de diseño: 2 x 51,9 m³/s / 176 Pa

Water distribution system:

- No. of pipes: 2 x 3
- Material : Polypropylene
- Flange connection: DN100 / PN 16
- No. of nozzles: 2 x 12
- Nozzle type: EWF-q 8 - EWF-q 16
- Header pressure: 3,840 m.c.a.
- Nozzle pressure: 20,0 - 60,0 kPa

Dimensions:

- Total width: 7.350 mm.
- Total length: 4.900 mm.
- Total height: 4.052 mm.
- Empty weight: 6.800 Kg.
- Operation weight: 9.500 Kg.